

CCD Color Camera Head

MODEL CN43H

Operation Manual

INFORMATION

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

USER-INSTALLER CAUTION: Your authority to operate this FCC verified equipment could be voided if you make changes or modifications not expressly approved by the party responsible for compliance to Part 15 of the FCC rules

This Class A digital apparatus complies with Canadian ICES-003.


Cet appareil numérique de la classe A est conforme à la norme NMB-003 du Canada.

CAUTIONS ON USE =

- Please use this apparatus by connecting only with camera control unit Elmo CC431E.
- Read the "CAUTIONS ON USE AND INSTALLATION" in the operation manual of CC431E, and follow

COMPONENTS (1) Camera head (without lens) (2) Accessory (a) Operation manual

CONNECTION



- When connecting or disconnecting the camera cables (for the camera head and camera control unit), always turn off the power switch of the camera control unit first. If not, the camera head may be damaged.
- Use a C-mount lens with the protruded section from the mount base less than 8.5

DISCLAIMER

user in any of the following cases

- 1. Fire, earthquake or any other act of God; acts by third parties; misuse by the user, whether inten-
- tional or accidental; use under extreme operating conditions.

 2. Malfunction or non-function resulting in indirect, additional or consequential damages, including

- 6. Notwithstanding the foregoing, ELMO's liabilities shall not, in any circumstances, exceed the purchase price of the product.

COPYRIGHT AND RIGHT OF PORTRAIT

CAUTIONS ON USE AND INSTALLATION

- Do not drop, or give a strong shock or vibration to the camera. This may cause problems. Treat the camera cables carefully to prevent cable problems, such as cable breakdown and loosened connections.
- may occur. When intense light enters, vertical stripes may appear on the screen. This is not a malfunction. Ghosts may occur when there is an intense light near the object. In this case, change the shooting angle.
- appear on the screen. In such a case, try to change the location of the camera or the cable wiring
- interference stripes. This is not a malfunction.

- Be particularly careful when using in places exposed to direct sunlight. When shooting in hot places depending on the conditions of the object and the camera (for example when the gain is increased), noise in the form of vertical strips or white dots may occur. This is not a malfunction.
- camera, do not throw away. When not using the camera for a longtime.
- Stop supplying power.
- Always turn off the power and clean with a piece of soft dry cloth. Do not use benzine, alcohol, thinner, household detergents, chemically treated cloths, etc. If used, coating and printed letters may be dis-
- colored. When cleaning the lens, use a lens cleaning paper, etc.
- Places near gasoline, benzene, or paint thinner.
- Places subject to strong vibration.

 Places contacting chemicals (such as pesticides), rubber or vinyl products for a long period of time.

SPECIFICATIONS

Image sensor	1/2 inch IT-CCD	
Effective pixels	Horizontal: 768 pixels, Vertical: 494 pixels	
Effective image area	Horizontal: 6.54 mm, Vertical: 4.89 mm	
Resolution	Horizontal: More than 470 lines, Vertical: More than 350 lines	
Standard intensity of illumination for objects	20 lx (F1.2, 3000K)	
Minimum intensity of illumination for objects	1.5 lx (F1.2, 3000K)	
S/N ratio	46 dB or more	
Lens mount	C-Mount	
Weight	2.8 oz (78g)	

• Design and specifications are subject to change without notice.

OPTIONAL PARTS

For further details, contact your Elmo dealer.

Camera control unit

Type name	
CC431E	

Camera cable

Type	Code #	Nominal length	Diameter
EMC-02H	9833	2m	5.0mm
EMC-03H	9833-1	3m	5.0mm
EMC-05H	9833-2	5m	5.0mm
EMC-12H	9833-3	12m	5.0mm
EMC-20H	9833-4	20m	5.0mm
EMC-30H	9833-5	30m	5.0mm
EMC-54H	9833-6	54m	5.0mm

EXTERIOR DIMENSIONS

Camera Head







Unit : mm [inch] ø : diameter

We disclaim any responsibility and shall be held harmless for any damages or losses incurred by the

- but not limited to loss of expected income and suspension of business activities.

 3. Incorrect use not in compliance with instructions in this instruction manual.
- 4. Malfunctions resulting from misconnection to other equipment
- 5. Repairs or modifications made by the user or caused to be made by the user and carried out by an unauthorized third party.

There may be a conflict with the Copyright Law and other laws when a customer uses, displays, distributes, or exhibits an image picked up by a television camera without permission from the copyright holder. Please also note that transfer of an image or file covered by copyright is restricted to use within the scope permitted by the Copyright Law.

- Carefully handle the units.
- Do not shoot intense light
- If there is an intense light at a location on the screen such as a spot light, a blooming and smearing
- If the camera or the cables are located near power utility lines or a TV, etc. undesirable noise may
- When thin stripe patterns are shot, stripe patterns that are not actually there (moire) may appears as
- Operating ambient temperature and humidity. Do not use the camera in places where temperature and humidity exceed the specifications. Picture quality will lower and internal parts may be damaged.
- Handling of the protection cap.
 Keep the protection cap away from children. Children may put them into mouth or swallow them accidentally. The protection cap protects the image sensing plane when the lens is removed from the
- When cleaning the camera
- Avoid using or storing the camera in the following places: Places filled with highly flammable gas.

ELMO CO., LTD. 6-14, Meizen-cho, Mizuho-ku, Nagoya, 467-8567 Japan

OVERSEAS SUBSIDIARY COMPANIES

ELMO Mfg. Corp.

1478 Old Country Road, Plainview, NY 11803-5034 U.S.A. Tel. 516-501-1400 Fax. 516-501-0429 E-mail:elmo@elmousa.com

44 West Drive, Brampton Ontario, L6T 3T6, Canada Tel. 905-453-7880 Fax. 905-453-2391 E-mail:info@elmocanada.com

Web:http://www.elmocanada.com

ELMO Canada Mfg. Corp. ELMO (Europe) G.m.b.H.

Neanderstr. 18 40233 Düsseldorf, Germany Tel. 0211-376051-53 Fax. 0211-376630 E-mail:elmoeurope@AOL.com Web:http://www.elmo.de

E[MO] and **E**:L.MI□ are registered trademarks of ELMO COMPANY, LIMITED.