

ELMO elite P2MP MAX

Powered by Circle Technology

LAN Interface	
Standard Compliance	IEEE802.3ab(1000 Base-T), IEEE802.3u(100 Base-TX), IEEE802.3(10 Base-T)
Speed and Flow Control	10/100/1000 Mbps
Number of LAN Ports	4
Connector Type	RJ-45
Other	
Dimensions	7.3 X 1.1 X 7.7
Weight	1.14 lbs
Operating Environment	32-104°F, 10-85% (non-condensing)
Power Consumption	8.2W Max
Power Supply	External, AC 100-240V input, 12V DC output
OS Compliance	Windows® 7 (32-bit/64-bit), Windows® 7 (32-bit/64-bit), Windows Vista® (32-bit/64-bit), Windows® XP, Mac OS® X
USB Interface	
Interface	USB 2.0 Type A
Number of Ports	1
Data Transfer Rates	480 Mbps
WAN Interface	
Standard Compliance	IEEE802.3ab(1000 Base-T), IEEE802.3u(100 Base-TX), IEEE802.3(10 Base-T)
Speed and Flow Control	10/100/1000 Mbps
Number of WAN Ports	1
Connector Type	RJ-45
Security	VPN pass through, PPTP Server, OpenVPN Server
Wireless LAN Interface	
Standard Compliance	IEEE802.11n, IEEE 802.11g, IEEE 802.11b, IEEE802.11a
Frequency Band	2.4 GHz / 5 GHz
Access Mode	Infrastructure mode, Ad-hoc mode
Antenna	2 X 2 Internal
Streams	2 X 2
Wireless Security	WPA2-PSK (AES, TKIP), WPA-PSK (AES, TKIP), 128/64-bit WEP