

ELMO elite P2MP Plus

Powered by Circle Technology

HARDWARE FEATURES	
Interface	1 10/100Mbps WAN/LAN Port 1 Micro USB Port 1 Reset Button
Wireless Standards	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Dimensions (W x D x H)	2.2 x 2.2 x 0.7 in. (57 x 57 x18 mm)
Antenna Type	On-Board
WIRELESS FEATURES	
Frequency	2.4-2.4835GHz
Signal Rate	11n: Up to 150Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
Reception Sensitivity	135M:-70dBm@10%PER 65M:-73dBm@10%PER 54M:-76dBm@10%PER
Transmit Power	CE: <20dBm(2.4GHz) FCC: <30dBm
Wireless Modes	AP Mode, Router Mode ,Client Mode, Repeater Mode, Bridge Mode
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless Security	64/128/152-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
SOFTWARE FEATURES	
WAN Type	Dynamic IP/Static IP/PPPoE/ PPTP/L2TP
DHCP	Server, Client, DHCP Client List, Address Reservation
Quality of Service	WMM, Bandwidth Control
Port Forwarding	Virtual Server, Port Triggering, UPnP, DMZ
Dynamic DNS	DynDns, Comexe, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec (ESP Head)
Access Control	Local Management Control, Host List, Access Schedule, Rule Management

SOFTWARE FEATURES	
Firewall Security	DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding
Management	Access Control Local Management Remote Management
OTHERS	
Certification	CE, FCC, RoHS
Package Contents	TL-WR702N Power Adapter USB Cable Ethernet cable Quick Installation Guide Resource CD
System Requirements	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7, MAC®OS, NetWare®, UNIX® or Linux
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing