

P10 Visual Presenter

# Set the stage for exceptional presentations



The P10 offers both exceptional image quality and flexibility for a variety of documents and media. Progressive scanning with a free-angle camera arm and detailed 48X zoom ensures crystal-clear imagery and captures moving objects at impressive frame rates. Several video output options let you connect to almost any monitor. Combined with built-in SD Memory Card support and a lightweight, compact design, the P10 is the ultimate in versatility and quality.







# **P10** Specifications

	odel		P10
Camera	Image pickup device		1/3" progressive scan CCD
	Total pixels		1,077 (H) x 788 (V), 850,000 pixels
	Effective pixels		1,034 (H) x 779 (V)
	Frame rate		20 fps
	Resolution	RGB output	600 (H) x 600 (V) TV lines
		Video output	450 (H) TV lines
Optics	Zoom		Powered (with variable speed function ),
			12X optical, 4X digital
	Lens		F2.8, f=4.7 to 56.4 mm
	Shooting area		Max. 405 x 303 mm (15 15/16" x 11 15/16"),
			min. 36.5 x 28 mm (1 7/16" x 1 3/32")
	Focus		Auto/Manual (powered)
	lris		Auto (with level adjustment)/Manual
Functions	White balance		Full-auto/One-push/Manual
	Negative/positive conversion		Provided
	Aperture enhancement		Provided
	Text mode		Provided
	Edge enhancement		Provided
	Color/B&W selection		Provided
	Pause mode		Provided
	Gamma adjustment		Provided
	OSD (on-screen display)		Provided
	Split display		Provided (SD Memory Card image, 9-split, 16-split)
	Image save		Provided (onto SD Memory Card )
	Image rotation		Provided (0°, 180°)
	State presetting		Up to 6 user settings
	Sync. system		Internal
Input/output	Internal selection		Int./RGB
	Analog RGB output		XGA (1,024 x 768 @60 Hz), VESA
	Video output		Composite, S-video
	RGB input		Provided
	DVI output		Provided
PC interface	RS-232C port		Provided
	USB port		Provided
Memory card	SD Memory (	Card slot	Provided
Lighting	Upper lighting		Provided (twin fluorescent lamp)
Others	Supplied accessories		I/R remote control, AC adapter, cables, etc.
	Dimensions	Set up	377 x 482 x 582 mm (14 27/32" x 18 31/32" x 22 29/32")
	(W x D x H)	Folded	377 x 482 x 180 mm (14 <sup>27</sup> /32" x 18 <sup>31</sup> /32" x 7 <sup>3</sup> /32")
	Weight		4.7 kg (10.4 lbs)
	i vveiant		
	-	oftware	Image Mate for Presentation, Image Mate for Movie
	Application s	oftware	Image Mate for Presentation, Image Mate for Movie Creation, TWAIN driver [for Windows® 2000 (SP4 or later
	-	oftware	Image Mate for Presentation, Image Mate for Movie Creation, TWAIN driver [for Windows® 2000 (SP4 or later Windows® XP (SP2 or later)]

H: horizontal, V: vertical


## Rear panel



Design and specifications are subject to change without prior notice.

🗲 💶 M 🕞 is a trademark of ELMO COMPANY, LIMITED. SD logo is a trademark. Other brand names and product names may be trademarks or registered trademarks of their respective owners.





# **Optional Accessories**



5-inch color LCD monitor LM-5011N Monitor shoe MS-30

Image Mate software for creating outstanding PC presentations

.....





Annotate your presentation right from a PC

Split Screen lets you compare live video to stored images







ELMO CO., LTD.(Head Office and Factory)'s QMS/EMS has been registered to ISO 9001:2000 & ISO 14001:2004.

Distributed by



FOCUS ON THE FUTURE

Additional technical information is available from any of the following subsidiary companies:

### ELMO USA Corp.

1478 Old Country Road Plainview, NY 11803-5034, U.S.A. Tel. 516-501-1400 Fax. 516-501-0429 E-mail: elmo@elmousa.com Web: http://www.elmousa.com

### ELMO Canada Corp. 44 West Drive, Brampton, Ontario, L6T 3T6, Canada

Tel. 905-453-7880 Fax. 905-453-2391 E-mail: info@elmocanada.com Web: http://www.elmocanada.com

ELMO CO., LTD. 6-14, Meizen-cho, Mizuho-ku,

Tel. 81-52-821-3141 Fax. 81-52-811-5243 E-mail: foreign-div@elmo.co.jp

Nagoya, 467-8567, Japan

ELMO (Europe) G.m.b.H. Neanderstr. 18, 40233 Düsseldorf, Germany Tel. 0211-3864-70 Fax. 0211-376630 E-mail: info@elmoeurope.com Web: http://www.elmoeurope.com

