

ELMO

HV-8000SX

SXGA-RESOLUTION NETWORK PRESENTER



Introducing the most advanced SXGA Presenter available anywhere. The ELMO HV-8000SX not only is a high performance and full-featured presenter, but it is also IP addressable.

What you expect from the world's #1 supplier of presenters - The latest technology, advanced features, quality & reliable performance.

SXGA-RESOLUTION NETWORK PRESENTER HV-8000SX

SPECIFICATIONS

Model	HV-8000SX
Power source	AC 100-240V, 50/60Hz
Lens	F2.8 f=7.2-72mm
Shooting area	Max: 362x290mm(14.3x11.4in.) Min: 40x32mm (1.6x1.3in.)
Camera head rotation	•
Zooming	10x (Powered)
Pre-set zoom	•
Electronic magnification	2x (Can be scrolled)
Focusing	
Auto	•
Manual	•(Powered)
Iris	
Auto	•(with level adjustment)
CCD	1/2
1,500K pixels	•
Analog RGB output	
SXGA (1280x1024 @60Hz)	•
XGA (1024x768 @60Hz)	•
Frame rate	7.5 fps
Video output	
NTSC Color	•
PAL Color	•
Composite	•
S-video (Y/C)	•
Resolution (TV lines)	
RGB output (HxV)	800x800
Video output (H)	400
White balance control	
Full-auto	•
One-push auto	•
Manual	•
Nega/Posi conversion	•
Color/B&W selection	•
Image rotation	•(90°, 180°, 270°)
Scrolling	•
Gamma adjustment	•
Aperture selection	•
Freeze (pause) function	•
Video pointer	•
OSD (On Screen Display)	•(Icon)
Sync. System	Internal
Internal selection	Int./RGB1/RGB2
RGB input	•(x2)
Audio input	•(Stereo) (x2)
Mic. Input	•
Built-in downconverter	•
Image output	
RGB	•
Composite video	•
S-video	•
Audio output	•(Stereo)
I/R remote control (supplied)	•
RS-232C port	•
Mouse port (mouse supplied)	•
USB port (image transfer)	•
LAN port	•
Via Web/LAN	
Internet browser	Internet Explorer, Netscape Navigator
Compression mode	JPEG
Image transfer resolution	
Still image	1280x1024, 640x512, 320x256
Live image	640x512
Remote control	Zoom, Focus, Iris, Lights, Nega/Posi, Color/B&W, RGB, Aperture, Contrast
Interface	10Base-T/100Base-TX Ethernet x 1
Protocol	TCP/IP, ARP, UDP, ICMP, HTTP, FTP, telnet
Image transfer to PC	•
DC 12V output	•
Lighting	
Upper lighting unit	•(Twin lamps)
Baselight	•
Carrying handle	•
Dimensions	
- When set-up (WxDxH)	766 x 449 x 628 mm (30.2 x 17.7 x 24.7in.)
- When folded	533 x 449 x 185 mm (21.0 x 17.7 x 7.3in.)
Mass/weight	10.5 kgs (23.2 lbs)



ELMO HV-8000SX can, via Web/LAN network,

- Transmit clear SXGA high-resolution image
- Send a real-time/live image
- Operate the Presenter from a remote location
- Share the document with others via the internet

ELMO HV-8000SX also offers;

- True SXGA (1280x1024) resolution plus NTSC/PAL Video output
- SXGA-quality 10x powered optical zoom lens plus electronic magnification
- I/R remote (supplied), Mouse (supplied), RS-232C controls
- USB port for image transfer to PC
- Industrially-designed twin lighting units
- Baselight for transparency
- Built-in downconverter
- Camera head turn with 180° image rotation
- OSD (On Screen Display) control with Icon

And MORE



ELMO CO., LTD. (Head Office and Factory)'s QMS/EMS has been registered to ISO 9001 & ISO 14001.

ELMO ELMO CO., LTD.

6-14, Meizen-cho, Mizuho-ku, Nagoya, 467-8567 Japan E-mail: foreign-div@elmo.co.jp

ELMO Mfg. Corp.

1478 Old Country Road,
Plainview, NY 11803-5034, U.S.A.
Tel. 516-501-1400 Fax. 516-501-0429
E-mail: elmo@elmousa.com
Web: <http://www.elmousa.com>

ELMO Canada Mfg. Corp.

44 West Drive, Brampton,
Ontario, L6T 3T6, Canada
Tel. 905-453-7880 Fax. 905-453-2391
E-mail: info@elmocanada.com
Web: <http://www.elmocanada.com>

ELMO (Europe) G.m.b.H.

Neanderstr 18,
40233 Düsseldorf, Germany
Tel. 0211-376051-53 Fax. 0211-376630
E-mail: elmo@elmo.de
Web: <http://www.elmo.de>