


ELMO EDR-X116 Rack Mount Chassis

X Series



FEATURES

- 16 video channel inputs @ 120 fps
- Simultaneous recording, playback, & remote access
- Digital watermark with verification software
- Call (spot) monitor output @ 30 fps
- LAN, WAN and dial-up connectivity (via TCP/IP) software provided
- P.O.S. and ATM ready (optional)
- Browser based monitoring
- Event log file function
- Backup remotely via static IP, LAN, or CD Burner
- Multiplexed output
- Remote software provided for infinite users
- PAN/TILT Zoom Control
- Intelli Guard/control output/email/dial up
- Health Checking Function

ELMO

ELMO EDR - X116 Rack Mount Chassis

Model Specifications

EDR-X116 - 16 video inputs 120 FPS

Video Input & Image Quality

Video input 1VPP, 75 OHM typical
Connector for BNC
Proprietary compression
Resolutions 160x120, 320x240, 640x480
Maximum display 16 cameras 120 fps
Maximum recording 1-4 cameras 120fps, 8 cameras 120fps, and 16 cameras 112fps

Video Output

Main monitor VGA (1024x768)
Connector type DB-15 HD (SVGA)
Call (spot) monitor 1Vpp, 75 OHM
Multiplexed output on monitor

Audio

Recording and playback 1 channel (line mic and line out)
Connectors are 1/8" mini phone jacks

Alarm Inputs and Outputs

Number of inputs & outputs: 16 (non isolated for dry contact sensors)
Connectors screw less & terminal blocks

Connectivity

LAN / WAN 10/100 Ethernet card
Modem
Connector (dial-up) DB-9 or telephone jack RJ-12
Transmission Speed LAN: 120 Frame/Sec, PSTN: 1-5 Frame/Sec, ISDN: 3-10 Frame/Sec

Hardware

PC based, Windows 2000™
Internal 180 GB hard disk drive (upgradeable to a total of 6 HD-with upgrade in Power Supply and IDE Card)
CDRW & 1.44 MB floppy drive
Pentium IV up to 1.8GHz or higher, 256 MB RAM, 64 MB Graphic Card

Electrical

Power source 115-120 VAC; 50-60 HZ switchable, maximum 350W

Mechanical

Rack mount design
Steel case

Environmental

Dimensions: 440mm wide x 452 mm deep x 175 mm high or (17.32"x17.8"x6.89")
Approx. weight: 40lbs or 18.18 kg
Operating Temperature: 5° to 40°C, 41° to 104°F
Operating Humidity below 90% RH

Warranty


Coverage provided is 3 years for parts & labor and 1 year parts & labor for hard drive
Shipping not included

Video Standards

NTSC/EIA is standard, while PAL CCIR is available upon request

Key Features and Benefits

- 1-16 video channel inputs
- Simultaneous recording and playback
- Digital watermark
- Printer hardcopy/JPEG/BMP to diskette
- Call (spot) monitor output
- LAN, WAN and dial-up connectivity (via TCP/IP)
- P.O.S. and ATM ready (optional)
- Web security ready (Browser Access)
- Event log file function
- 'Video Loss' or 'No Video Alarm' when camera(s) off will control the relay output
- Drop/drag pictures on the remote
- Backup remotely via static IP or LAN & CD Burner
- PAN/TILT Zoom Control
- Intelli Guard/control output/email/dial up/voice command
- I.P.C.O.



ELMO

ELMO Mfg. Corp.
1478 Old Country Road
Plainview, New York 11803
Tel. 516.501.1400
Fax. 516.501.0429
www.elmousa.com

ELMO Canada Mfg. Corp.
44 West Drive Brampton,
Ontario, L6T 3T6, Canada
Tel. 905-453-7880
Fax. 905-453-2391
www.elmocanada.com